



**Hornady**  
*Accurate. Deadly. Dependable.*

# L-N-L<sup>®</sup> Impact Bullet Puller

Item No. 050092



## Setup/Assembly

Make sure all parts are included and in good condition.

## Using the Impact Bullet Puller

- The Impact Bullet Puller comes with three collets. The small collet (with three rings) is for .22 Hornet and similar-diameter cases. The medium collet (two rings) is for most rifle and pistol cases. The large collet (one ring) is for most belted magnums, Winchester Short Magnum (WSM), Remington Ultra Magnum (RUM) and similar-diameter cases.
- Choose the correct collet and place it inside the plastic cap so the flat side of the collet fits with the handle side of the bullet puller. Screw the cap onto the handle. Loosen the cap a few turns and insert a cartridge, bullet first. Push the cartridge in until the extractor groove clamps into the collet or, with a rimmed cartridge, until the top of the collet touches the rim. Tighten the cap.
- Hold the bullet puller like a hammer and tap the opposite end of the cap on a hard surface. Keep tapping the bullet puller until the bullet is released from the cartridge. Once the bullet has been removed, the powder will pour into the bullet puller. Remove the cap of the bullet puller, dump the powder out and remove the case.

## Collet Storage

- Your Impact Bullet Puller features a collet storage compartment at the base of the handle that stores two collets. Be advised that if only one collet is stored inside the handle, the collet will rattle around.
- To open the handle's storage compartment, hold the Impact Bullet Puller so the base of the handle is facing up.
- With the H logo closest to you, rotate the storage cap counter clockwise 1/8th of a turn and pull up.

## WARNING

***Using this bullet puller to disassemble certain types of ammunition can result in a cartridge explosion with the potential of personal injury and/or property damage.***

- Do not attempt to disassemble ANY rimfire cartridges (22 Short, Long or Long Rifle, for example)
- Do not attempt to disassemble ANY ammunition identified as “Explosive”, “Observation”, “Spotting”, or “Incendiary”.
- Do not use this bullet puller to disassemble ANY cartridge with a high primer.
- Do not use with black powder cartridges
- Do not attempt to disassemble ANY cartridge whose projectile type cannot be positively identified.
- **IF IN DOUBT OF THE AMMUNITION TYPE, DO NOT ATTEMPT TO DISASSEMBLY BY ANY MEANS**

Do not use heavy blows to remove a bullet. Failure to heed this warning may result in a cartridge explosion with the potential for property damage and/or personal injury. A series of short, sharp taps will remove most bullets effectively. If bullet shows no signs of movement from the case after a series of short, sharp taps do not continue to use the Hornady L-N-L® Impact Bullet Puller. For rifle cartridges, use the Hornady Cam Lock Bullet Puller. Primers are sensitive objects that will react to impact.

Wear safety glasses during all reloading operations, including bullet pulling, to protect your eyes in the event of an explosion.

Do not attempt to reload with salvaged propellant powder unless you are absolutely certain of its identity. If in doubt, discard the powder.

Since Hornady has no control over the choice of components, the manner in which they are assembled, the use of this product, or the firearms in which the resulting ammunition may be used, no responsibility, either expressed or implied, is assumed for the use of ammunition reloaded with this product.



**Hornady®**  
*Accurate. Deadly. Dependable.*

P.O. Box 1848, Grand Island, Nebraska 68802-1848  
308-382-1390 • 800-338-3220 • Fax: 308-382-5761  
[www.hornady.com](http://www.hornady.com) • [Hornady.com/contact\\_us](http://Hornady.com/contact_us)